

便携式移动演播室

4通道HDBaseT移动会议录播一体机**HS-1600T MARK II**

视频系统	HD & SD
视频格式	1080p 50/59.94/60Hz 1080i 50/59.94/60Hz 720p 50/59.94/60Hz 576i/p 50Hz 480i/p 59.94Hz
输入格式设定	----
视频输入	3 x HDBaseT 1 x HDMI
计算机输入	1 via HDMI
下变换转换器	Yes
视频输出	3x HDMI PGM 1x HDBaseT PGM 1x STREAM (RJ-45)
音频输入	2x Balanced XLR 1x Stereo RCA (L/R) De-embedded Digital Audio
音频输出	1x Stereo headphone
音频嵌入	Input 2 channels, Output 2 channels
音频延迟	----
音频同步切换	----
USK	1x USK support Lumakey
DSK	----
画中画	1
LOGO	----
字幕机	----
调音台	Yes, 4 channels
监看屏幕	17.3" HD TFT LED backlit, 1920x1080 pix
通话系统	----

直播串流规格

串流视频编码	H.264 / AVC, Main/ High Profile Configurable Bit-rate up to 10Mbps
串流音频编码	AAC-LC Configurable bit rate range from 32Kbps to 384Kbps Sample rate: 48KHz, 16bit

串流协议	TS over TCP/UDP (unicast & multicast) RTSP over HTTP/TCP/UDP (RTSP Elementary Streaming) RTMP/RTMPS (Publish) HLS SRT
串流控制	Web browser UI for configuration and control Socket commands
录制设定控制	Web UI for system configuration and control
录制文件系统	FAT, exFAT, NTFS

其他规格

特别功能	Built-in camera controller
尺寸	455 x 355 x 134 mm
重量	17.2 Lbs (7.8 kg), Reinforce Plastic Case
电源	DC 48V, 4.16A
操作温度	0~40 °C
包装明细	1 x HS-1600T MARK II Product 1 x AD Switch DC 56V with AC Cord 3 x Ethernet Cable