

摄控一体摄像机

**HD/SD 云台摄像机 (HDBaseT)****PTC-150T**

视频格式	1080p 59.94/50/29.97/25 1080i 59.94/50 720p 59.94/50 480i, 576i (on CVBS)
感光元件	1/2.8" type progressive scan CMOS sensor
有效像素	2.14 Mega pixels
信噪比	50dB
最低照度	Color : 0.4 lx B/W : 0.03 lx (F1.6, 1/30 sec, 50IRE, Gain: High)
电子快门	1/25~1/1250 sec (50/25Hz) 1/30~1/1500 sec (59.94/29.97Hz)
镜头	30x Optical Zoom
伽马设定	Off / Normal / Standard Mode 1-4
光圈设定	Auto / Manual
数字降噪	Yes
选单语言	English
白平衡	AWB, MWB, One push WB, Outdoor, Indoor, Fluorescent
AGC/增益控制	Auto / Manual Max. Gain Limit
镜头翻转	Yes
对焦模式	Auto / Manual
水平/垂直范围可动角度	Pan: 270° , Tilt: +90° to -20°
水平/垂直移动速度	Manual: 1~150°/Sec Swing: 1~150°/Sec
预设点	50 Position
焦距	f=4.3 mm (WIDE) to 129 mm (TELE) F1.6 to F4.7
视角	Approx. 63.7° (WIDE END) / 2.3° (TELE END)
图像补偿	Day & Night function
视频输出接口	HDMI (V1.3) x 1 3G-SDI x 1 CVBS x 1 HDBaseT x 1 to PTC-150T Receiver Box
音频输入接口	----
TALLY灯	Dual color (Red, Green)
滤片或广角镜	M52.0 x 0.75 Thread with UV Protection
控制协议	VISCA, DVIP

远程控制接口	RS-422: Transmit up to 1000m HDBaseT (RJ-45)/ DVIP on Receiver Box: Transmit up to 100m
视频压缩格式	----
音频压缩格式	----
音频比特率	----
高清IP接口	----
串流协议	----
第一串流直播分辨率	----
第二串流直播分辨率	----
视频比特率	----
视频比特率模式	----
编码帧率	----
POE模块	----
固件更新	USB
IR控制	Yes
摄像机控制器	HS-1500T/HS-1600T series/RMC-180 series/RMC-300 series
脚架用螺丝尺寸	1/4-20 UNC
可选附件	WM-1/ WM-10/ WM-11
颜色	Dark Blue/White
尺寸	173 x 189 x 219 mm
重量	2.7 kg
操作温度	0~40 °C
电源	DC 12V 29W
包装明细	1 x PTC-150T/TW Unit 1 x HBT-11 Receiver Box 1 x IR remote controller 1 x Ceiling mount bracket-A 1 x Ceiling mount bracket-B 6 x Ceiling mount bracket screw M3*4mm 1 x DC 12V Power Adaptor 1 x DC 48V Power Adaptor 2 x Power Cord 1 x A tightrope 1 x Phoenix connector to RJ-45