

摄控一体摄像机

4K 云台摄像机**PTC-280**

视频格式	HDMI: 2160p 60/59.94/50/30/29.97/25 1080p 60/59.94/50/30/29.97/25 1080i 60/59.94/50 720p 60/59.94/50 SDI: 1080p 60/59.94/50/30/29.97/25 1080i 60/59.94/50 720p 60/59.94/50 (2160p 60/59.94/50 YUV 4:2:0 only)
感光元件	1/2.5" CMOS
有效像素	8.51Mega Pixels
信噪比	≥55dB
最低照度	0.5 Lux @ (F1.8, AGC ON)
电子快门	1/30s ~ 1/10000s
镜头	12x Optical Zoom, 16x Digital Zoom
伽马设定	Off / Normal
光圈设定	Auto / Manual
数字降噪	2D/3D
选单语言	English/Simplified Chinese/Traditional Chinese
白平衡	Auto, Indoor, Outdoor, OnePush, Manual, VAR
AGC/增益控制	Yes
镜头翻转	Yes
对焦模式	Auto/Manual
水平/垂直范围可动角度	Pan: 300° Tilt: +130° to -15°
水平/垂直移动速度	Pan: 0.876°/s~43°/s Tilt: 0.693°/s ~21.32°/s
预设点	255
焦距	12x, f = 4.4mm ~ 52.8mm, F1.8 ~ F2.6
视角	71°
图像补偿	Back light compensation
视频输出接口	HDMI 2.0 x1 3G-SDI x1 10/100/1000M RJ45 x1
音频输入接口	3.5mm x1
TALLY灯	Yes

滤片或广角镜	N/A
控制协议	Pelco-D, Peldo-P, VISCA, VISCA over IP DHCP, RTSP, RTMP (IP Cam), RTMPS, DVIP
远程控制接口	IR Web UI RS-422 DVIP
视频压缩格式	H.264/H.265/MJPEG
音频压缩格式	AAC
音频比特率	96Kbps, 128Kbps, 256Kbps
高清IP接口	----
串流协议	TCP/IP, HTTP, RTSP, RTMP(S), SRT, ONVIF, DHCP, Multicast
第一串流直播分辨率	3840x2160 1920x1080 1280x720 1024x576 960x540 640x480 640x360
第二串流直播分辨率	1280x720 1024x576 720x576 (50Hz) 720x480 (60Hz) 720x408 640x360 480x270 320x240
视频比特率	32Kbps ~ 50Mbps (Single Stream)
视频比特率模式	VBR, CBR
编码帧率	50Hz: 1-50fps 60Hz: 1-60fps
POE模块	IEEE 802.3AT
固件更新	Via Web UI or USB 2.0
IR控制	Yes
摄像机控制器	RMC-180 series/RMC-300 series/PTZ View Assist APP
脚架用螺丝尺寸	1/4-20 UNC
可选附件	WM-1/ WM-10/ WM-11
颜色	Dark Blue/White
尺寸	173 (W) x 219 (H) x 189.08 (D)
重量	2.8 kg
操作温度	0~40 °C
电源	DC 12V

包装明细

1 x PTC-280 product
1 x IR remote controller
1 x Ceiling mount bracket-A
1 x Ceiling mount bracket -B
6 x Ceiling mount bracket screw M3*4mm
1 x DC 12V Power Adaptor
1 x A tightrope