

摄控一体摄像机

4K NDI 云台摄像机**PTC-280NDI**

| | |
|-------------|--|
| 视频格式 | HDMI: 2160p 60/59.94/50/30/29.97/25 1080p 60/59.94/50/30/29.97/25 1080i 60/59.94/50 720p 60/59.94/50 SDI: 1080p 60/59.94/50/30/29.97/25 1080i 60/59.94/50 720p 60/59.94/50 (2160p 60/59.94/50 YUV 4:2:0 only) |
| 感光元件 | 1/2.5" CMOS |
| 有效像素 | 8.51Mega Pixels |
| 信噪比 | ≥55dB |
| 最低照度 | 0.5 Lux @ (F1.8, AGC ON) |
| 电子快门 | 1/30s ~ 1/10000s |
| 镜头 | 12x Optical Zoom, 16x Digital Zoom |
| 伽马设定 | Off / Normal |
| 光圈设定 | Auto / Manual |
| 数字降噪 | 2D/3D |
| 选单语言 | English/Simplified Chinese/Traditional Chinese |
| 白平衡 | Auto, Indoor, Outdoor, OnePush, Manual, VAR |
| AGC/增益控制 | Yes |
| 镜头翻转 | Yes |
| 对焦模式 | Auto/Manual |
| 水平/垂直范围可动角度 | Pan: 300° Tilt: +130° to -15° |
| 水平/垂直移动速度 | Pan: 0.876°/s~43°/s Tilt: 0.693°/s ~21.32°/s |
| 预设点 | 255 Position |
| 焦距 | 12x, f = 4.4mm ~ 52.8mm, F1.8 ~ F2.6 |
| 视角 | 71° |
| 图像补偿 | Back light compensation |
| 视频输出接口 | HDMI 2.0 x1 3G-SDI x1 10/100/1000M RJ45 x1 |
| 音频输入接口 | 3.5mm x1 |
| TALLY灯 | Yes |

| | |
|-----------|--|
| 滤片或广角镜 | N/A |
| 控制协议 | Pelco-D, Peldo-P, VISCA, VISCA over IP DHCP, RTSP, RTMP (IP Cam), RTMPS, DVIP NDI |
| 远程控制接口 | IR Web UI RS-422 DVIP NDI |
| 视频压缩格式 | H.264/H.265/MJPEG |
| 音频压缩格式 | AAC |
| 音频比特率 | 96Kbps, 128Kbps, 256Kbps |
| 高清IP接口 | --- |
| 串流协议 | TCP/IP, HTTP, RTSP, RTMP(S), SRT, ONVIF, DHCP, Multicast |
| 第一串流直播分辨率 | 3840x2160 1920x1080 1280x720 1024x576 960x540 640x480 640x360 |
| 第二串流直播分辨率 | 1280x720 1024x576 720x576 (50Hz) 720x480 (60Hz) 720x408 640x360 480x270 320x240 |
| 视频比特率 | 32Kbps ~ 50Mbps (Single Stream) |
| 视频比特率模式 | VBR, CBR |
| 编码帧率 | 50Hz: 1-50fps 60Hz: 1-60fps |
| POE模块 | IEEE 802.3AT |
| 固件更新 | Via Web UI or USB 2.0 |
| IR控制 | Yes |
| 摄像机控制器 | RMC-180 series/RMC-300 series/PTZ View Assist APP |
| 脚架用螺丝尺寸 | 1/4-20 UNC |
| 可选附件 | WM-1/ WM-10/ WM-11 |
| 颜色 | Dark Blue/White |
| 尺寸 | 173 (W) x 219 (H) x 189.08 (D) |
| 重量 | 2.8 kg |
| 操作温度 | 0~40 °C |
| 电源 | DC 12V |

| | |
|------|--|
| 包装明细 | 1 x PTC-280NDI product 1 x IR remote controller 1 x Ceiling mount bracket-A 1 x Ceiling mount bracket -B 6 x Ceiling mount bracket screw M3*4mm 1 x DC 12V Power Adaptor 1 x A tightrope |
|------|--|