

切换台

**HD 6通道切换台****SE-1200MU**

|           |  |
|-----------|--|
| 视频系统      | HD   |
| 视频格式      | 1080i 50/59.94/60Hz<br>720p 50/59.94/60Hz  |
| 视频处理      | SDI: 4:2:2<br>HDMI: YUV 4:2:2 10 bit, RGB 4:4:4  |
| 输入设置[XPT] | All 6, repeatable  |
| 视频输入      | 4x HD-SDI<br>2x HDMI (RGB/YUV, 1080i/1080p/720p)   |
| 相容高标清     | ----   |
| 电脑连接      | 2 via HDMI   |
| 视频输出      | 2x HD-SDI<br>2x HDMI assignable:<br>PGM(w/DSK 1&2), PGM(w/DSK 1), PGM Clean, PVW(w/o DSK), multi-view, Input 1-6 |
| 下转输出      | ----   |
| 多分割画面监看   | HDMI & SDI assignable, Ethernet (MJPEG)  |
| 音频输入      | 2x Balanced XLR  |
| 音频输出      | ----   |
| 支持音频轨数    | Input 2 channels, Output 2 channels  |
| 音频延迟      | ----   |
| 音视频同步切换   | Yes  |
| 视频抠像      | 2  |
| 字幕机       | ----   |
| USK       | 2x Keyer support Chromakey/ Linear/ Luma Key   |
| DSK       | 2x DSK support Lumakey/ Linear key (Key / Fill)  |
| 子母画面      | 1  |
| LOGO显示    | ----   |
| 内置静帧图片    | 500  |
| 转场效果      | FTB, Cut, 32 Wipe with border  |
| 过场预览      | Full transitions preview   |
| 同步信号输入/输出 | Built-in Genlock (internal)  |
| Tally输出   | 1x D-sub 15pin, dual color   |
| 电脑控制      | Ethernet (free Window software)<br>RS-422/ RS-232  |
| 调音台       | ----   |

|      |   |
|------|---|
| 特別功能 | Motion JPEG Multi-view streaming<br>(120 memory preset, BGD Transition on/off option)<br>Free Virtual Set and Stinger transition included |
| 外型   | 1RU rack-mount mainframe  |
| 尺寸   | 440 x 215 x 49 mm   |
| 重量   | 1.5 kg  |
| 电源   | DC 12V, 19W   |
| 操作溫度 | 0~40 °C   |
| 包装明细 | 1 x SE-1200MU product<br>1 x AD Switch DC 12V<br>1 x DB9P TO DB9P Cable<br>2 x 1U Rack Mount Ear<br>6 x M4 Screws for Rack Mount Ear      |