

切换台

HD 12通道切换台

SE-3200

视频系统	Full HD
视频格式	1080p 50/59.94/60Hz 1080i 50/59.94/60Hz 720p 50/59.94/60Hz
视频处理	SDI: 4:2:2 HDMI: YUV 4:2:2, RGB: 4:4:4
输入设置[XPT]	All 12, repeatable
视频输入	8x SDI, 4x HDMI
相容高标清	----
电脑连接	4 via HDMI
视频输出	6x SDI Outputs assignable: Multiview, PGM, PVW, PGM+DSK, Clean PGM, Clean PVW, Input 1-12, STILL 1, STILL 2, Flex source 3x HDMI assignable: Multiview, PGM, PVW, PGM+DSK, Clean PGM, Clean PVW, Input 1-12, STILL 1, STILL 2, Flex source
下转输出	1x SDI
多分割画面监看	HDMI & SDI assignable
音频输入	4x Balanced XLR
音频输出	2x Balanced XLR
支持音频轨数	Input 2 channels, Output 4 channels
音频延迟	Up to 16 fields or 8 frames per channel
音视频同步切换	Yes
视频抠像	4
字幕机	Yes, CG-200 software free download
USK	4x Keyer support Chromakey/ Linear/ Luma Key
DSK	2x DSK support Lumakey & Linear key (Key / Fill)
子母画面	8 (4x PIP, 4x Flex Source)
LOGO显示	2
内置静帧图片	999+
转场效果	DVE, FTB, Cut, 32 Wipe with border
过场预览	Full transitions preview
同步信号输入/输出	Built-in Genlock Support external sync with loop thru
Tally输出	1x D-sub 25pin, dual color
电脑控制	RS-232 / DVIP (Ethernet)
调音台	----

特別功能	4 User Memory Preset Free Virtual Set and Stinger transition included
外型	2 units, 2RU rack-mount mainframe
尺寸	433 x 312 x 76 mm (switcher) 432 x 252 x 88 mm (main unit)
重量	4 kg
电源	DC 12V, 69W
操作溫度	0~40 °C
包装明细	1 x SE-3200 Main Unit 1 x SE-3200 Control Board 2 x AD Switch DC 12V 1 x AC Cord 1 x DB9P TO DB9P Cable 12 x Screw 2 x 2U Ear Rack