

Datavideo Product Compare

<https://test.datavideo.cn/>

Model Number	CAP-2
Product	HDMI 视频采集盒
输入	1x HDMI
输出	1x USB 3.0 (Micro B)
输入视频带宽	150MHz (pixel clock rate)
输出视频带宽	Up to 350Mbps (USB)
输入视频格式	1920 x 1080p 60/59.94/50/30/29.97/25/24/23.976 1920 x 1080i 60/59.94/50 (de-interlaced out) 1680 x 1050p 60 1600 x 1200p 60 1440 x 900p 75/60 1400 x 1050p 60 1366 x 768p 60 1360 x 768p 60 1280 x 1024p 75/60 1280 x 720p 60/59.94/50 1024 x 768p 75/60 800 x 600p 75/60 720 x 576p 50 720 x 480p 60 640 x 480p 60

输出视频格式	1920 x 1080p 60/50/30/25/24 1680 x 1068p 60 1440 x 1080p 60 1440 x 896p 60 1360 x 768p 60 1280 x 768p 60 1280 x 720p 60/50 1024 x 768p 60 960 x 536p 60 848 x 480p 60 768 x 576p 60 720 x 480p 60/50 640 x 480p 60 640 x 360p 60
音频输入	HDMI Embedded Audio & 3.5 mm stereo in
音频格式	2-Channel, 44.1KHz and 48KHz sample rate embedded in, up to 24-bit PCM, fixed 48KHz output
摄取视频格式	YUY2 (USB3.0), MJPG (USB2.0/3.0)
固件升级	Via USB Port
软件兼容性	Windows: Amcap, Google Plus Hangouts, OBS (Open Broadcast Software), Skype, VLC, Xsplit Broadcaster, Zoom.us Linux: VLC, OBS Mac OS X: OBS, Quicktime player, VLC, Facetime
支持系统	Windows® 7(SP1) / Windows 10 / Windows 8.1 / Windows 7 (x86, x64), OS X (10.10 or above), Linux Ubuntu 14.04
电源提供方式	Via USB
电源	2W
工作温度	0~40°C
储存温度	-20~60°C
湿度	20~90% RH (no condensation)
系统配置要求	Windows® 7(SP1) / Windows 10 / Windows 8.1 / Windows 7 (x86, x64) Note: The driver is required for Windows 7 OS OS X (10.10 or above) Linux Ubuntu 14.04 PC: Intel® Core™ i5-4440 3.10GHz + NVIDIA® GeForce® GTX 660 or higher Laptop: Intel® Core i7-4810MQ + NVIDIA GeForce GTX 870M or higher 4GB RAM or higher

尺寸(LxDxH)	105 x 68 x 23 mm
重量	70g
包装明细	1 x CAP-2 1 x USB 3.0 Cable