

Datavideo Product Compare

<https://test.datavideo.cn/>

Model Number	ITC-300
Product	数字导播通话系统
Tally 接口	2 x 15 Pin D-Sub Female Sockets for Tally A and Tally B
耳机麦克风接口	1 x 3.5mm Stereo Jack Socket (For Headphone / Microphone combination) Headset Impedance 24 ohm 100mW(min) Microphone Level -45.2dB (Tip: Mic□Ring: Phone□Sleeve: GND)
耳机接口	1 x 1/4" (6.3mm) Stereo Headphone Socket (Tip: Phone□Ring: Phone□Sleeve: GND)
灯光接口(DC 12V)	Light Power Consumption: +5 V / 500 mA
麦克风接口	3 Pin XLR / 1/4" (6.3mm) Socket x 1 Switchable Condenser / Dynamic Input Microphone Level -67dB PIN1:N/A,PIN2:MIC,PIN3:GND
频率响应	300 Hz-7 KHz, < +/-3dB
总谐波失真(THD)	< 0.1% @1KHz
信号杂讯比(S/N)	>70dB
内建麦克风	3W Speaker is mute when headphones or mic / headset are connected to the ITC-300
操作范围	Up to 100m between Base Station and Slave
操作温度	0~40 °C

尺寸	440 x 126 x 44mm
重量	1.9 kg
电源	DC 12V, 3A
包装明细	1 x ITC-300 Base Unit 4 x ITC-300SL Belt Pack 4 x Ethernet Cable 4 x Earphone Cable 4 x Headset with microphone 1 x Gooseneck Microphone 1 x Tally LED Indicator 4 x Velcro 1 x USB Gooseneck Light 1 x Adaptor + AC Cord