

Datavideo Product Compare

<https://test.datavideo.cn/>

Model Number	SE-1200MU
Product	HD 6通道切换台
视频系统	HD
视频格式	1080i 50/59.94/60Hz 720p 50/59.94/60Hz
视频处理	SDI: 4:2:2 HDMI: YUV 4:2:2 10 bit, RGB 4:4:4
输入设置 □XPT□	All 6, repeatable
视频输入	4x HD-SDI 2x HDMI (RGB/YUV, 1080i/1080p/720p)
相容高标清	----
电脑连接	2 via HDMI
视频输出	2x HD-SDI 2x HDMI assignable: PGM(w/DSK 1&2), PGM(w/DSK 1), PGM Clean, PVW(w/o DSK), multi-view, Input 1-6
下转输出	----
多分割画面 监看	HDMI & SDI assignable, Ethernet (MJPEG)
音频输入	2x Balanced XLR
音频输出	----
支持音频轨 数	Input 2 channels, Output 2 channels
音频延迟	----

音视频同步切换	Yes
视频抠像	2
字幕机	----
USK	2x Keyer support Chromakey/ Linear/ Luma Key
DSK	2x DSK support Lumakey/ Linear key (Key / Fill)
子母画面	1
LOGO显示	----
内置静帧图片	500
转场效果	FTB, Cut, 32 Wipe with border
过场预览	Full transitions preview
同步信号输入/输出	Built-in Genlock (internal)
Tally输出	1x D-sub 15pin, dual color
电脑控制	Ethernet (free Window software) RS-422/ RS-232
调音台	----
特别功能	Motion JPEG Multi-view streaming (120 memory preset, BGD Transition on/off option) Free Virtual Set and Stinger transition included
外型	1RU rack-mount mainframe
尺寸	440 x 215 x 49 mm
重量	1.5 kg
电源	DC 12V, 19W
操作温度	0~40 °C
包装明细	1 x SE-1200MU product 1 x AD Switch DC 12V 1 x DB9P TO DB9P Cable 2 x 1U Rack Mount Ear 6 x M4 Screws for Rack Mount Ear

