

Datavideo Product Compare

<https://test.datavideo.cn/>

Model Number	SE-2200
Product	HD/SD 6通道切换台
视频系统	HD & SD
视频格式	1080i 50/59.94/60Hz 720p 50/59.94/60Hz 576i 50Hz 480i 59.94Hz
视频处理	SDI: 4:2:2 HDMI: YUV 4:2:2 10 bit, RGB 4:4:4
输入设置 □XPT□	All 6, repeatable
视频输入	6x HD-SDI, 2x HDMI (on CH5 & 6)
相容高标清	----
电脑连接	2 via HDMI
视频输出	6x SDI Outputs assignable: AUX 1-4, PGM, PVW, PGM Clean & multi-view 2x HDMI assignable: PGM or multi-view
下转输出	----
多分割画面 监看	2x HDMI
音频输入	4x Balanced XLR
音频输出	2x Balanced XLR

支持音频轨数	Input up to 16 channels, Output 4 channels
音频延迟	----
音视频同步切换	Yes
视频抠像	----
字幕机	Yes, CG-200 software free download
USK	----
DSK	2x DSK support Lumakey/ Linear key (Key / Fill)
子母画面	2
LOGO显示	2 (or 1 logo + 1 clock)
内置静帧图片	6
转场效果	FTB, Cut, 8 Wipe with border
过场预览	PiP & DSK
同步信号输入/输出	Built-in Genlock (internal)
Tally输出	1x D-sub 25pin, dual color
电脑控制	Ethernet (free Window software) RS-422/ RS-232
调音台	----
特别功能	6x 6 Matrix seamless switch Built inTC-200 CG interface
外型	2 units, 2RU rack-mount mainframe
尺寸	433 x 312 x 76 mm (switcher) 432 x 252 x 88 mm (main unit)
重量	6.1 kg
电源	DC 12V, 32W
操作温度	0~40 °C

包装明细

1 x SE-2200 Main Unit
1 x SE-2200 Key Board
1 x AD Switch DC 12V with AC Cord
1 x DB9P TO DB9P Cable
1 x CB-41 / XLR to XLR Cable
12 x Screw
2 x 2U Ear Rack