

Datavideo Product Compare

<https://test.datavideo.cn/>

Model Number	SE-2850-12
Product	HD/SD 12通道切换台
视频系统	HD & SD
视频格式	1080p 25/29/30/50/59.94/60Hz 1080i 50/59.94/60Hz 720p 50/59.94/60Hz 576i 50Hz 480i 59.94Hz
视频处理	SDI: 4:2:2 HDMI: YUV 4:2:2 10 bit, RGB 4:4:4
输入设置 □XPT□	All 12, repeatable
视频输入	Standard: 8x SDI, 2x HDMI Max: 12x SDI, 3x HDMI
相容高标清	Yes
电脑连接	Max 3 via HDMI
视频输出	4x SDI assignable: PGM, PVW, AUX & Clean Out 2x HDMI assignable: PGM & multi-view
下转输出	4x SDI
多分割画面 监看	2x HDMI
音频输入	4x Balanced XLR
音频输出	2x Balanced XLR

支持音频轨数	Input up to 16 channels, Output 4 channels
音频延迟	Up to 8 frames per channel(*SDI input audio only)
音视频同步切换	Yes
视频抠像	----
字幕机	Yes, CG-200 software free download
USK	----
DSK	2x DSK support Lumakey/ Linear key (Key / Fill)
子母画面	2
LOGO显示	2 (or 1 logo + 1 clock)
内置静帧图片	12
转场效果	FTB, Cut, 8 Wipe with border
过场预览	PiP & DSK
同步信号输入/输出	Built-in Genlock Support external sync with loop thru
Tally输出	1x D-sub 25pin, dual color
电脑控制	Ethernet (free Window software) RS-422/ RS-232
调音台	----
特别功能	4-CH SD downconvert output Built in TC-200 CG system Selectable SMPTE/EBU Audio level
外型	2 units, 2RU rack-mount mainframe
尺寸	433 x 312 x 76 mm (switcher) 432 x 252 x 88 mm (main unit)
重量	4.7 kg
电源	DC 12V, 44W
操作温度	0~40 °C

包装明细

- 1 x SE-2850 Main Unit
- 1 x SE-2850 Control Board
- 1 x AD Switch DC 12V with AC Cord
- 1 x DB9P TO DB9P Cable
- 1 x CB-41 / XLR to XLR Cable
- 2 x Extra button cap for wipe
- 12 x Screw
- 2 x 2U Ear Rack